SPECIFICATION



www.winkelmann.co.uk



THROUGH-WALL AUDIO AND TACTICAL SURVEILLANCE

Super-directional: hear only what is inside the target roor

High intelligibility listening through 50cm concrete wall

Thin, ultra sensitive probe microphone (*optional)

Ruggedised sensor withstands high impact forces

Completely passive sensor with no metal or electrical par

Optical fiber connection over extended lengths

Light weight sensor (less than 30g)

Difficult to detect (by conventional ways)

Low Power consumption (10mA or less)

Work in high humidity conditions

Suited for use in SWAT, tactical task forces

Localization of target's inside a room

Battery operation time up to 24 hours

Echo cancellation to headphones Ideal for permanent installations

External power connection
Absolute EMI/RFI immunity

Sensitive to vibrations

Harsh environments

2 Year Warranty

Listening through walls, doors, windows

Extremely high sensitivity and gain

Wide frequency range: up to 8000Hz

Adaptive noise reduction DSP (*optional)

Built-in recorder (*optional)

Battery operated

Line out for recording

Weather-proof sensors

Mounting Kit

E	SO30 - WOODPECKER SSO30 - WOODPECKER SSO30 - WOODPECKER SSO40 - WOODPECKER SSO40 - WOODPECKER SSO40 - WOODPECKER SSO50 - SUPERBAT UITMATE SSO50 - WAND Directional Contact Microphone Directional Contact Microphone Directional Contact Microphone SSO50 - WAND SSO50 - WAND Through Wall Sound Detector										
	30S	30A	40	50	60	80	80U	90	90P		
	'	>	'	V	/	/	/	V	~		
						/	~	~	'		
m						/	~	~	'		
						/	V	~	V		
			/ *		/	/	~	~	V		
						/	>	~	V		
			*		*	*	>		'		
						*	>				
				/		/	>	/	V		
	~	/	~	V	/	/	V	/	V		
	~	/	~	V	/	/	V		'		
	~	/			/	~	~				
						/	>				
			/		>	>	>				
				/				/	V		
								~	V		
			V		/						
	/	/			/	/	V				
	~	/	~		/	/	~				
			~		/						
rts			~		/						
			~		>						
	~	/	~		/						

1